

Cordons LANmark-6A Ultim UniBoot

LANmark-6A Ultim Patch Cord Cat 6A Screened LSZH 2m Orange

Code article Nexans: N11A.U1F0200K

- Cordons RJ45 avec des performances élevées afin de supporter le protocole 10GBase-T et les futures applications Catégorie 6A / Classe EA
- Supportent une haute densité : 48 cordons sur 1 HU
- Gamme de fréquence jusqu'à 500MHz, totalement conforme aux standards Catégorie 6A TIA568B.2-10 et ISO11801 (2010) A2
- Paires écrantées individuellement pour une diaphonie interne réduite et une immunité à la diaphonie exogène (Alien Crosstalk)
- Certificat de conformité externe
- Manchons de protection amovibles et disponibles en 8 couleurs

Description

Application

LANmark-6A Ultim cords are developed to support 10 Gigabit Ethernet (IEEE 802.3an) and any other future Cat.6A application.

LANmark-6A Ultim Cords offer superior performance up to 500MHz and are matched with other LANmark-6A components to provide improved data throughput in complex channel configurations. Ultim cords use stranded cable and as such provide maximum system flexibility for the use at Cross Connects and Consolidation points.

They will also maximise the lifetime and longevity of the system by minimising the risk of wear & tear damage. Due to their good electrical performance and mechanical stability, LANmark-6A Ultim cords can be used for accurate field testing of Cat 6A cabling channels. .

Ultim Cords feature a slim boot for mechanical protection, which is kept inside the RJ45 boundaries to enable High Density Patching with 48 cords in 1 height unit.

They also come with a 'Replaceable' Latch Protector, which can be used for colour coding of different services.

Performance

The LANmark-6A Ultim cords fully comply and exceed the requirements of EIA/TIA-568-B.2-10 and ISO11801 A2 and enable to achieve high performing Cat 6A channels. Used with other LANmark-6A components, very short Cat 6A link and channel configurations with up to 3 connection points within 10 meters can be supported.

Garantees

When installed in combination with other LANmark-6A components, a 25 years channel warranty can be obtained, covering full 10GBase-T support and full Cat 6A/Class EA compliance.



LANmark-6A

Normes

Internationales EN 50173-1;
IEEE 802.3an; ISO/IEC 11801:2002/
Amd 1:2008/Cor 1:2008; ISO/
IEC TR24750; ISO/IEC 11801:2002/
Amd 2:2010/Cor 1:2010

Nationales ANSI/TIA-568-C.2; TIA/
EIA TSB-155



Non propagateur de l'incendie
IEC 60332 Part 1

Cordons LANmark-6A Ultim UniBoot

LANmark-6A Ultim Patch Cord Cat 6A Screened LSZH 2m Orange

Usage

- The cords are by design fully Alien Crosstalk compliant, so no special installation rules need to be taken into account for ANEXT and AFEXT compliance.
- 1, 2, 3, 5, 10, 20m are standard lengths available from stock, other lengths are available on demand.
- Orange and Dark Grey are standard colours available from stock; other colours are available on demand.
- Default Plug Configuration is a black boot with a preinstalled black latch protector.

Caractéristiques

Caractéristiques de construction	
Couleur	Orange
Ecran	Yes
Gaine extérieure	LSZH-FR
Caractéristiques dimensionnelles	
Diamètre externe nominal (mm)	6,0 mm
Caractéristiques électriques	
Impédance caractéristique	100 Ohm
Caractéristiques d'utilisation	
Gamme	LANmark-6A
Longueur	2 m
Durée de vie mécanique à l'insertion	750
Non propagateur de l'incendie	IEC 60332 Part 1
Fonction du composant	Cordon
Catégorie	Cat. 6A
Conditionnement	Box of 50 items



Non propagateur de l'incendie
IEC 60332 Part 1

Cordons LANmark-6A Ultim UniBoot

LANmark-6A Ultim Patch Cord Cat 6A Screened LSZH 2m Orange

Performances électriques du Channel LANmark-6A Classe EA 4 connecteurs Partie 1

"All values are based on Worst Case 4 Connector Channel configurations according to ISO 11801. Minimal and maximum values represent guaranteed channel performance"

Freq in MHz	Attn in dB		NEXT in dB			PSNEXT in dB			ACR-F in dB	
	Max	Typ	Std	Min	Typ	Std	Min	Typ	Std	Typ
1	<4	4.0	65.0	67.0	85.0	62.0	64.0	74.8	63.3	69.9
4	4.1	4.1	63.0	65.0	72.9	60.5	62.5	65.0	51.2	57.9
10	6.4	6.3	56.6	58.6	65.0	54.0	56.0	58.5	43.3	49.9
16	8.1	8.0	53.2	55.2	60.9	50.6	52.6	55.1	39.2	45.9
20	9.1	9.0	51.6	53.6	59.0	49.0	51.0	53.5	37.2	43.9
31.25	11.4	11.2	48.4	50.4	55.1	45.7	47.7	50.2	33.4	40.0
62.5	16.3	15.9	43.4	45.4	49.1	40.6	42.6	45.1	27.3	34.0
100	20.8	20.2	39.9	41.9	45.0	37.1	39.1	41.6	23.3	29.9
155	26.2	25.4	36.7	38.7	41.2	33.8	35.8	38.3	19.5	26.1
200	30.0	28.9	34.8	36.8	39.0	31.9	33.9	36.4	17.2	23.9
250	33.8	32.5	33.1	35.1	37.0	30.2	32.2	34.7	15.3	22.0
300	37.3	35.7	31.7	33.7	35.4	28.8	30.8	33.3	13.7	20.4
500	49.3	46.7	27.9	29.9	31.0	24.8	26.8	24.9	9.3	16.0

*Standard values based on ISO 11801 Class EA



Non propagateur de l'incendie
IEC 60332 Part 1

Cordons LANmark-6A Ultim UniBoot

LANmark-6A Ultim Patch Cord Cat 6A Screened LSZH 2m Orange

Performances électriques du Channel LANmark-6A Classe EA 4 connecteurs Partie 2

All values are based on Worst Case 4 Connector Channel configurations according to ISO 11801. Minimal and maximum values represent guaranteed channel performance

Freq in MHz	PS ACR-F in dB		PS ANEXT in dB			PS AACR-F in dB			RL in dB		
	Std	Typ	Std	Min	Typ	Std	Min	Typ	Std	Min	Typ
1	60.3	66.9	80.0	90.0	92.0	77.0	92.0	94.0	19.0	21.0	21.0
4	48.2	54.9	74.0	89.0	91.0	65.0	80.0	82.0	19.0	21.0	32.0
10	40.3	46.9	70.0	85.0	87.0	57.0	72.0	74.0	19.0	21.0	28.0
16	36.2	42.9	68.0	83.0	85.0	52.9	67.9	69.9	18.0	20.0	26.0
20	34.2	40.9	67.0	82.0	84.0	51.0	66.0	68.0	17.5	19.5	25.0
31.25	30.4	37.0	65.1	80.1	82.1	47.1	62.1	64.1	16.5	18.5	23.1
62.5	24.3	31.0	62.0	77.0	79.0	41.1	56.1	58.1	14.0	16.0	20.0
100	20.3	26.9	60.0	75.0	77.0	37.0	52.0	54.0	12.0	14.0	18.0
155	16.5	23.1	57.1	72.1	74.1	33.2	48.2	50.2	10.1	12.1	16.1
200	14.2	20.9	55.5	70.5	72.5	31.0	46.0	48.0	9.0	11.0	15.0
250	12.3	19.0	54.0	69.0	71.0	29.0	44.0	46.0	8.0	10.0	14.0
300	10.7	17.4	52.8	67.8	69.8	27.5	42.5	44.5	8.0	10.0	13.2
500	6.3	13.0	49.5	64.5	66.5	23.0	38.0	40.0	8.0	10.0	11.0

*Standard values based on ISO 11801 Class EA



Non propagateur de l'incendie
IEC 60332 Part 1