

SNOM D385 DESKPHONE



Features:

- 12 SIP identities / accounts
- XML browsers
- Call lists for dialed, received, missed calls
- Local directory with 1000 entries
- Multiple language support
- DTMF in-band / out-of-band / SIP-INFO
- Interoperable with all major IP PBX platforms

Call Features:

- Speed dialing
- URL dialing
- Local dial plan
- Automatic redial on busy
- Call completion (busy/unreachable) (2)
- Caller identification
- Call waiting
- Call blocking (deny list)
- Auto answer
- Hold
- Music on hold (2)
- Handling of up to 12 simultaneous calls
- Blind and attended transfer
- Call forwarding
- 3-way conferencing on the phone
- Extension monitoring, call pickup (2)
- Call park, call unpark (2)
- Multicast paging
- DND mode (do not disturb)
- Keyboard lock

Setup:

- Configurable through web interface
- Provisioning:
 - Automatic loading of settings via HTTP/HTTPS/TFTP
 - DHCP Option 66/67
 - Snom Redirection Service
 - Remote management via TR_069 / TR-111

Protocols:

- SIP (RFC3261)
- DHCP, NTP
- HTTP / HTTPS / TFTP
- LDAP (Directory)
- Dual Stack IPv4 / IPv6

User Interface:

- Localization (language, time, dial tone)
- RED LED for call indication / message waiting
- 4 context-sensitive keys
- 48 (12) configurable self-labeling LED keys
- Dedicated keys for: Message, DND, Directory
- Menu, Transfer, Hold, Page switch
- Audio keys: Mute, Speakerphone, Headset
- Volume key
- 4-way navigation key
- OK and Cancel keys
- Menu-driven user interface

- Client matter code (CMC) (2)

Audio:

- Codecs:
 - G.711 A-law, μ -law
 - G.722 (wideband)
 - G.726, G.729AB, GSM 6.10 (FR)
- Built-in assignable ringtones
- Comfort Noise Generator (CNG)
- Voice Activity Detection (VAD)

Phone Features:

- Dimensions (approx.): 250 x 185 x 120mm (LxWxH)
- Weight (approx.): 880g
- Input voltage: 5Vdc (SELV)
- Power supply: PoE or 5Vdc power adapter (1), 10 Watts
- Handset: 4P4C
- Headset: 4P4C; support for Snom EHS Advanced
- Hearing-aid compatible (HAC) handset
- 1x USB 2.0 host port: Type A
- Environmental conditions:
 - Ambient temperature: 0°C to 35°C (32°F to 95°F)
 - Storage temperature: -10°C to 45°C (14°F to 113°F)
 - Humidity: 5% to 95% (non-condensing)
- Included in delivery:
 - Phone unit
 - Footstand
 - Handset with cord
 - Ethernet cable
 - Quick Start Guide
- Colour: black blue
- Warranty: 2 Years

Security:

- 802.1X authentication and EAPOL
- Transport layer security (TLS)
- SRTP (RFC3711), SIPS, RTCP
- HTTPS server/client
- Password-protected web interface
- VPN-support
- VLAN (IEEE 802.1Q)
- LLDP-MED, RTCP-XR

Type Approvals:

- CE Mark
- Safety IEC 60950, CB

(1) Optional accessory (see below for part numbers)

(2) If supported by PBX

Part numbers:

00004325 Power Adapter Snom A6 / EU clip
 00004326 Power Adapter Snom A6 / US clip
 00001168 UK clip for Snom A6
 00004327 D3 Expansion Module
 00002362 Snom EHS Advanced
 00004387 DECT-Headsets Snom A170
 00004341 Monaurales Headset Snom A100M
 00004342 Binaurales Headset Snom A100D
 00004343 ACUSB Headset adaptor
 Deskphones
 00004340 Snom D385
 00004141 Snom D375
 00004260 Snom D345
 00004258 Snom D315
 00004257 Snom D305

snom